

WAYNESFIELD RACEWAY PARK
2017 1000CC Upright Mini Sprint Rules

If you are running a "Built" engine (head work or non OEM pistons) then you must add 75 lbs of weight. Weight must be painted white with your car number written on it clearly. Weight must be fastened securely to the chassis.

PLEASE NOTE THAT AFTER THE 2017 SEASON NO MORE BUILT ENGINES WILL BE ALLOWED!!!

1. ENGINE

- a. 4 cylinder, 4 cycle motorcycle engine only. Stock 1000cc maximum. **Stock bore and stroke.**
- b. Stock ignition box.
- c. Electric self starting.
- d. Fuel injected. Alcohol conversions allowed.
- e. 6 inch offset-measured C/L of motor and C/L of the frame.
- f. Stock OEM pistons**
- g. Stock OEM rods**
- h. Stock bottom end (crank)**
- i. Stock head (No porting/polishing)**
- j. Milling head is legal**
- k. Dry sump is allowed**
- l. Mechanical injection is okay**
- m. Degree cams are legal**
- n. Charging system must be operational and without on/off switch**

2. WEIGHT

- a. The weight of the car at the conclusion of any race must be a minimum of 900 lbs for gas engines, 925 lbs for alcohol engines and 875lbs. with driver, for any 600cc cars (no sidewinders).

3. TRANSMISSION

- a. On all engines, clutch must be in place and operational (no bypass). Clutch basket and clutch spring tension can be changed.
- b. Stock configuration in any gear engine must roll over or shift and must be operational. All gears must work.**

4. DRIVE SYSTEM

- a. Final drive must come from original counter shaft, drive must be chained to rear axle.

5. CARBURETOR OR FUEL INJECTION

- a. May run on gas or alcohol. No nitro or nitrous oxide.
- b. No turbo, super chargers, or vacuum pumps.

6. BODY SPECS.

- a. Must have complete midget style body, suitable bumpers, both front and rear nerfbars to extend out from chassis or body to a minimum of rear tire center line.
- b. No components are to be outside of frame excluding header or muffler.
- c. Secure rear bumpers and side nerfbars mandatory to compete.

7. FRAME AND ROLL CAGE SPECS.

- a. Wheel base 65"-74", Tread width 40"-52" center to center. Engine must remain within 6" offset of Centerline of frame.
- b. Roll cage must be constructed of 1 1/8-.083 wall round tubing minimum in chrome-moly or equivalent in Mild steel.
- c. Cage must extend at least 2" above driver's helmet.

8. WINGS

- a. 12 or 16 square-Outside edge of side boards must remain inside of rear tire tread Front wing permitted.

9. TIRE SPECS.

- a. Must be a Hoosier tire on all 4 corners of the car. Any compound.

10. WHEELS

- a. 13" only

11. No Muffler Rule

12. Protest Fee-1stPlace Money

13. 20 lap "A" Main

14. Competition green to get tow money

15. Transponders must be used. Can be rented at the track or purchased. Westhold (yellow)

Rechargeable units must be mounted close to right rear torsion tubes foil label side down.

16. Raceceivers are required. Default channel.

The absence of a specific rule does not imply approval, consent, or permission regarding the subject.

IF IT IS NOT MENTIONED IN THE ABOVE RULES... DON'T TRY IT!

Anyone disobeying these rules will be dealt with accordingly!

If You Have Any Questions Please Call 419-604-0288